



- Scansione omnidirezionale o a singola linea
- Prestazioni Elevate
- Design robusto ed ergonomico
- Installazione semplificata

Elegante e funzionale, dal design innovativo il lettore da banco AXON serie CS-6000 si integra in qualsiasi ambiente di lavoro.

Dotato di segnalatore acustico con volume regolabile, può essere impiegato in ambienti con elevato rumore o in quelli più discreti.

Il lettore da banco AXON serie CS-6000 dispone di lettore laser omnidirezionale, capace di leggere 20 linee per 1200 scansioni al secondo e decodifica codici 1D e GS1 Databar.



AXON Computer

Via Taliercio, 7/A
30030 - Gardigiano di Scorzè (VE)
Italy
Tel: +39.041.5830594
Fax: +39.041.5830595
E-mail: info@axoncomputer.it
www.axoncomputer.it

OPERATIONAL

Light Source	650 nm visible laser diode (VLD)
Depth of Field	0 - 216 mm (UPC/EAN 100%, PCS=90%)
Scan Pattern	5 directions of scan field
Scan Rate	1,200 scans per second (omnidirectional)
Number of Scan Lines	20
Minimum Bar Width	5 mil @ PCS=90%
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Two-color LED (green, red)
Beeper Operation	Programmable tone & volume
System Interfaces	Keyboard wedge, RS-232, HID USB

PHYSICAL

Dimensions	(L)118.0 × (W)100.0 × (H)165.1 mm
Weight	360 g (without cable)
Cable	Standard 2.0M straight

POWER

Input Voltage	5 VDC ±10%
Power Consumption	1.35 watts
Operating Current	270 mA (typical); 350 mA (peak)

REGULATORY

Laser Class	CDRH Class IIa; IEC 60825-1: Class 1
EMC	CE EN55022 B, FCC Part 15 Class B, VCCI, BSMI

ENVIRONMENTAL

Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	5% - 90% RH (no dewing allowed)
Light Levels	Up to 4,000 Lux (fluorescence)
Drop Durability	Designed to withstand 1.0M drops

Marchi e denominazioni appartengono ai loro rispettivi proprietari

Direzione Commerciale

Via Napoli, 125 - c/o Centro Commerciale Meridiana - 80013 Casalnuovo (NA) - Tel. +39.081.3176051